


Technical data sheet

Modular housing system · LCOS Modular housing system

Carrier base: Construction width without supply: 35 mm

Data bus 12-pole power bus AC/DC 500 V, 4×16 A

Integrated PE contact



Identification

Type	LCOS-FGO-350-01/00/01-1
Part No.	780103.350.1

Product version

Datasheet version	01
-------------------	----

Description

System Components	Function housing
Description	Function housing 35 mm, with cooling slits, closed front plate, connection opening top/bottom

General

Housing material	PA 6.6 (UL 94 V-0, NFF I2, F2)
Color of the housing	basalt grey
Mounting	on LCOS function carrier
Marking	3 × Labelling plates 5×5 mm
Power Dissipation	9 W @ 20°C, 4 W @ 60°C, 3 W @ 75°C
Degree of protection	IP20
Dimensions (w × h × d)	35.0 mm × 110.0 mm × 74.0 mm
PU (units)	1

General ambient conditions

Operation temperature range	-40 °C ... +85 °C
Storage temperature range	-40 °C ... +85 °C

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

Technical data sheet

Modular housing system · LCOS Modular housing system

Relative air humidity 5 – 95 %, no defrosting

Dimensions

