

Technical data sheet

Load monitoring · LOCC-Box Accessories

LOCC-Box supply set 16 mm²

Consisting of supply terminal and end block

Maximum total current 40 A (UL: 35 A)



Identification

Type	LOCC-Box-ES16 7-6447
Part No.	716447

Product version

Datasheet version	02
-------------------	----

Input

Rated voltage U_N	DC 12/24/48 V
Rated current I_N	Max. DC 40 A
Reverse voltage protection	No
Connection type input	Spring terminal 0.33 mm ² – 16 mm ² AWG 22 – AWG 6
Conductor connection cross section	Single-wire: max. 16 mm ² Finely stranded: max 10 mm ² Finely stranded with AEH: max 10 mm ²
Strip length	18 mm

Output

Rated voltage U_N	DC 12/24/48 V
Output current	Max. DC 40 A
Connection type output	Screwless contact slide
Copper bus bar	3 × 10mm

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

24.04.2024 • Subject to technical modification

Part No. [716447](#) • Datasheet version: 02

page 1 of 4

Technical data sheet

Load monitoring · LOCC-Box Accessories

General

Accessories	Supply set 16 mm ²
Connection type	Spring terminal Single wire/fine wire 1.50 mm ² – 16 mm ² AWG 16 – AWG 5 Fine stranded wire with ferrule Finely stranded, ferrule with plastic collar 1.5 mm ² – 10 mm ² AWG 16 – AWG 7 UL Values AWG 14 – AWG 6
Strip length	18 mm
Housing material	PA 6.6 (UL 94 V-0, NFF I2, F2)
Mounting	DIN rail mountable TS35 (EN 60715)
Degree of protection	IP20 (only as complete system with supply terminal, end block and copper rail cover)
Installation position	Any
Dimensions (w × h × d)	11.7 mm × 119.5 mm × 62.0 mm 10.0 × 119.5 × 62.0 mm
Weight/unit	0.045 kg
PU (units)	1

General ambient conditions

Operation temperature range	-25 °C ... +50 °C
Storage temperature range	-40 °C ... +85 °C
Relative air humidity	10 % – 95 %, without condensation
Vibration resistance	4 g acc. to EN 60068-2-6
Shock resistance	15 g acc. EN 60068-2-27


Certifications/Standards

Certifications	cULus (E135145)
Standards	UL 60947-5-1 DNVGL-CG-0339 Temperature Class D – not certified Humidity Class B – not certified Vibration Class B – not certified Enclosure Class A – not certified

Technical data sheet

Load monitoring · LOCC-Box Accessories


Dimensions



DE Endblock
EN End block
FR Bloc d'extrémité

DE Einspeiseklemme
EN Supply terminal
FR Borne d'alimentation


PIN assignment



Use


DE Standard Anwendung
EN Standard Application
FR Application standard

L = 18 mm + 8,1 mm x n **6**
L = 18 mm + 8,1 mm x n **5**




*n= LOCC-Box Module/Modules
/Modules


DE Anwendung mit Einspeiseklemme und Einspeisekl. mit Ausbruch mittig
EN Standard application with supply terminal and supply terminal cutout center
FR Application standard avec borne d'alimentation et borne d'alimentation avec encoche au milieu



DE Anwendung mit Einspeiseklemme und Einspeisekl. mit Ausbruch rechts
EN Standard application with supply terminal and supply terminal cutout right
FR Application standard avec borne d'alimentation et borne d'alimentation avec encoche à droite



DE Anwendung mit Einspeiseklemme und Einspeisekl. mit Ausbruch links
EN Standard application with supply terminal and supply terminal cutout left
FR Application standard avec borne d'alimentation et borne d'alimentation avec encoche à gauche



DE

- 1 Einspeiseklemme aus Set 716425/ 716447
- 2 Überwachungsbaustein – LOCC-Box
- 3 Endblock aus Set 716425/ 716447
- 4 Einspeiseklemme mit Ausbruch (716421)
- 5 Kupferschiene (716426/ 716426.xxx.x)
- 6 Abdeckung Kupferschiene (716427)

EN

- 1 Supply terminal from set 716425/ 716447
- 2 Monitoring Module – LOCC-Box
- 3 End terminal from set 716425/716447
- 4 Supply Terminal with outage (716421)
- 5 Copper rail (716426/ 716426.xxx.x)
- 6 Cover copper rail (716427)


FR

- 1 La borne de raccordement au réseau se trouve dans le kit 716425/ 716447
- 2 Convertisseur de mesure – LOCC-Box
- 3 Borne d'extrémité est inclus dans le kit 716425/ 716447
- 4 Borne d'alimentation avec encoche (716421)
- 5 Barre de cuivre (716426/ 716426.xxx.x)
- 6 Recouvrement pour rail cuivre (716427)

Technical data sheet

Load monitoring · LOCC-Box Accessories

Use



Use

