

Technical data sheet

Actuator sensor interface · M12 - connector

Field wireable connector, M12 straight, shielded

Female S coded, 690 V AC/12 A, 4-pin, cable diameter 6 – 11 mm

Spring terminal: Push-in connection technology, 0.75 – 2.5 mm²



Identification

Type	KUGK-M12(C) 4-POL-S FK
Part No.	490255

Product version

Datasheet version	00
-------------------	----

General

Design	Female Straight M 12 Shielded
Over voltage category	III
Degree of pollution	3
Flamability according to UL 94	V0
Degree of protection	IP65
Housing material	Brass, nickel plated
Contact material	Gold-plated
Thread material	Brass, nickel plated
Material knurled nut	Brass, nickel plated
Cable diameter	6 mm – 11 mm
Temperature range connector	-40 °C ... +85 °C
Dimensions (Ø×d)	Ø 23 × 68 mm
Contact durability	≥100
Connection type	Push-In spring connection

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

12.02.2025 • Subject to technical modification

Part No. [490255](#) • Datasheet version: 00

page 1 of 3

Technical data sheet

Actuator sensor interface · M12 - connector

Cross-section, metric	2.5 mm ² –1.5 mm ² with ferrule: 0.75–2.5 mm ² rigid: 1.5 mm ² –1.5 mm ²
Cross-section AWG	Without ferrule: AWG16–AWG14 With ferrule: AWG18–AWG14
Strip length	10 mm
Tightening torque	M12-knurled nut: 0.6 Nm Pressure nut with sleeve housing: 5 Nm
Pin configuration	1 = BK1 2 = BK2 3 = BK3 PE = GNYE
Weight/unit	0.092 kg
PU (units)	1


Technical data

Rated voltage U _N	AC 690 V
Measurement surge voltage	6 kV
Rated current	12 A
Pole number	4
Coding	S
Shielding	shielded

Certifications/Standards

Standards	based on IEC 61076-2-111
-----------	--------------------------


Dimensions



Technical data sheet

Actuator sensor interface · M12 - connector

Mounting diagram



Pin layout

M12 female
S-coded

