

Technical data sheet

PVC servo cables · shielded

LUTZE SILFLEX® M (C) PVC SERVO 0.6/1 kV

Motor/energy supply cable for Siemens and other systems



Identification

Type	SI M (C) PVC SE (4G1,5+(2×1,5)) 0,6/1kV
Part No.	116427
SIEMENS designation*	1BA11

Product version

Datasheet version	01
-------------------	----

Use/Application/Properties

Application	• For Siemens 6FX5008* standard system (and similar) • Termination cable motor or motor/brake especially for frequency converters and SERVO drives in machine and plant construction, transport and conveyor technology • Flexible design for easy installation • Suitable for static laying and slight movement of machine components (not C-track) • Low capacitance for high dielectric strength for long cable lengths from inverter to motor • In dry and damp rooms • Especially for industrial environments in mechanical and system engineering
Properties	• Low capacitance for high dielectric strength • High protection against electromagnetic interferences (EMI) • PVC Flame-retardant, self-extinguishing • Orange RAL 2003 per DESINA • Largely resistant to oils, greases, alcohol-free benzines and kerosene • Silicone free

Construction

Description	SILFLEX® M (C) PVC SERVO 0.6/1 kV
Number of conductors/cross-section	(4G1.5+(2×1.5))
Number of conductors	6
Cross-section AWG	AWG 16

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

20.03.2025 • Subject to technical modification

Part No. [116427](#) • Datasheet version: 01

page 1 of 3

Technical data sheet

PVC servo cables · shielded

Jacket material	Special PVC
Jacket color	orange similar to RAL 2003
Outer Ø	10.2 mm
Outer Ø	0.401 inch
Surface	adhesion-free
Weight	17.8 kg/100 m
Weight	119.26 Lbs/Mft
Cu-Index	15 kg/100 m
Cu-Index	104 Lbs/Mft
Cable construction	Construction with one signal pair (white, black)

Construction Element 1

Element construction	4G1.5
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 5 Finely stranded DIN VDE 0295 Class 5
Conductor marking	According to system manufacturer
Conductor insulation	TPE

Construction Element 2

Element construction	(2×1.5)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 5 Finely stranded DIN VDE 0295 Class 5
Conductor marking	According to system manufacturer
Conductor insulation	TPE
Stranding	Conductors stranded in pairs
Element shielding	Braid shield optical cover approx. 85% tinned copper wires

Overall construction

Overall stranding	Elements stranded together Layer pitch optimised Conductors twisted without mechanical stress
Overall wrapping	Foil taping Over the cable core Non-woven material
Overall shield	Braid shield Tinned copper wires Optical cover approx. 85 %

Technical data sheet

PVC servo cables · shielded

Jacket characteristics	Flame-retardant Self-extinguishing Silicone free Oil resistant Grease-resistant Petrol-resistant (alcohol-free) Kerosene-resistant
------------------------	--

Technical data

Rated voltage U_0/U	600/1000 V
Rated voltage UL	1000 V
Test voltage type	AC 4000 V
Temperature range moving	-5 °C ... +80 °C
Temperature range fixed	-20 °C ... +80 °C
Minimum bending radius moving	10×D
Minimum bending radius fixed	2.5×D

Technical Data Element 1

Element construction	4G1.5
Insulation resistance at 20 °C	≥1000 MΩ×km
Operating capacitance wire-wire	max.73 pF/m
Operating capacitance wire-shield	max.150 pF/m

Technical Data Element 2

Element construction	(2×1.5)
Insulation resistance at 20 °C	≥1000 MΩ×km
Conductor resistance	≤15 Ω/km
Operating capacitance wire-wire	max.125 pF/m
Operating capacitance wire-shield	max.230 pF/m

Certifications/Standards

Certifications	cURus
UL style	AWM 2570
Conformity	CE RoHS REACH
Burning behavior according to	DIN EN 60332-1-2 UL Cable Flame Test (UL 1581) CSA FT 1
Oil resistant according to	ISO 6722

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU * SIEMENS article designations are registered trademarks of SIEMENS AG
------	--