

Technical data sheet

Flexible VFD Cable 2kV RHW-2 with 3 Symmetrical Grounds for Stationary Applications · shielded

LUTZE DRIVEFLEX® XLPE (C) 2kV SYMMETRICAL



Identification

Type VFD XLPE 3 (C) PVC (3×AWG2+3×AWG10)
Part No. [A2190203](#)

Product version

Datasheet version 01

Use/Application/Properties

- Application
- Dual-shielded motor supply cable to connect power to 3-phase-motors, VFDs and servo drives
 - Three insulated symmetrical ground design helps to reduce stray currents
 - 2kV cable design for the most demanding VFD applications
 - Cable design for harsh industrial environments and operating conditions with high noise levels
 - Thermoset XLPE insulation offering superior overload and short-circuit temperature
 - Increased wall thickness insulation type RHW-2, offering lower capacitance and higher impedance making it ideal for applications with high voltage spikes and long cable runs
 - Compliant with NFPA 79 requirements
 - TC-ER for use with cable trays without conduit, which can reduce installation costs in industrial environments
 - WTTC – wind turbine tray cable rating for use in wind power generation
 - Dry, damp or wet conditions
- Properties
- Flexible XLPE conductors
 - Three symmetrical grounds (PE)
 - High insulation resistance
 - Low capacitance cable
 - Effective dual layer shield for EMC compliance
 - Specially formulated jacket for oil resistance and easy strip design
 - Non-wicking fillers
 - Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
 - Crush impact resistant
 - Gas/vapor-tight sheath per UL 1277
 - Sunlight resistant
 - Flame retardant
 - Direct burial
 - Talc free and silicone free

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

19.04.2024 • Subject to technical modification
Part No. [A2190203](#) • Datasheet version: 01

Technical data sheet

Flexible VFD Cable 2kV RHW-2 with 3 Symmetrical Grounds for Stationary Applications · shielded

Construction

Description	DRIVEFLEX® 3 SYMMETRICAL GROUNDS
Number of conductors/cross-section	(3×AWG2+3×AWG10)
Number of conductors	6
Cross-section, metric	35 mm ²
Cross-section AWG	AWG 2
Jacket material	PVC
Jacket color	black similar to RAL 9005
Outer Ø	31.5 mm
Outer Ø	1.24 inch
Weight	1.294 Lbs/Mft
Cu Index	880 Lbs/Mft

Construction Element 1

Element construction	AWG2/03C
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire Class K
Conductor marking	black · with white number print
Conductor insulation	XLPE RHW-2

Construction Element 2

Element construction	AWG10/03C
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire
Conductor marking	green/yellow · green/yellow · green/yellow

Overall construction

Overall stranding	elements stranded together
Drain wire	CU-wire tin-plated
Overall shield	Foil shield Aluminium laminate Braid shield tinned copper wires
Jacket characteristics	Oil resistant Silicone free

Technical data

Rated voltage U _N	2000 V 90C TC-ER 2000 V Flexible VFD servo cable 90C 1000 V WTTC 90C
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	7.5×cable OD

Technical data sheet

Flexible VFD Cable 2kV RHW-2 with 3 Symmetrical Grounds for Stationary Applications · shielded

Technical Data Element 1

Element construction AWG2/03C

Technical Data Element 2

Element construction AWG10/03C

Approvals/Standards

Approvals	cULus W TTC TC-ER cUL TC CIC FT4 Meets NEC 336, 392 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 UL 1277 UL 2277 Wet/Dry P-07-KA130021-MSHA
Conformity	CE RoHS REACH
Oil resistant according to	Oil Res II

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

PIN assignment

