

Technical data sheet

Flexible Control and Tray Cable with Blue Conductors for 24V Applications · Unshielded

LÜTZE SILFLEX® Tray-ER Blue PVC



Identification

Type SI N TRAY-ER Blue 7×AWG18 GR
Part No. [A3251807](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Multi-wire control cables with TC-ER „Exposed Run“ approval
 - Machine tools, machine and plant construction, VAC technology as well as other uses.
 - Compliant with NFPA 79 requirements
 - Blue conductors indicating 24 Volt circuits
 - MTW Machine Tool Wire
 - TC-ER for use with cable trays without conduit, which can reduce installation costs in industrial environments
 - Dry, damp or wet conditions
- Properties
- Specially formulated gray PVC jacket for oil resistance
 - Crush impact resistant
 - Gas/vapor-tight sheath per UL 1277
 - Non-wicking fillers
 - Sunlight resistant
 - Flame-retardant
 - Direct burial
 - Talc free and silicone free

Construction

Description SILFLEX® TRAY-ER BLUE PVC
Number of conductors/cross-section 7×AWG16
Number of conductors 7
Cross-section, metric 1 mm²
Cross-section AWG AWG 18
Jacket material PVC
Jacket color grey similar to RAL 7001
Outer Ø 9.4 mm
Outer Ø 0.373 inch
Weight 89 Lbs/Mft

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

03.07.2023 • Subject to technical modification

Part No. [A3251807](#) • Datasheet version: 00

page 1 of 2



SYSTEMATIC TECHNOLOGY

Technical data sheet

Flexible Control and Tray Cable with Blue Conductors for 24V Applications · Unshielded

Cu Index 42 Lbs/Mft

Construction Element 1

Element construction	AWG18/7C
Conductor construction	AWG 18 (19/30)
Conductor	AWG conductor CU-wire bare
Conductor category	fine wire Class K
Conductor marking	blue • with white number print • green/yellow • with number print 2 • white/ blue
Conductor insulation	PVC/Nylon THHN – THWN

Overall construction

Jacket characteristics Oil resistant
Silicone-free

Technical data

Rated voltage U_N	600 V TC-ER 90C 600 V UL MTW
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	4×cable OD

Technical Data Element 1

Element construction AWG18/7C

Approvals/Standards

Approvals	TC-ER UL Type MTW or DP-1 Meets NEC 336,392 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 cUL TC CIC FT4 UL 1277
Conformity	RoHS REACH TSCA
Oil resistant according to	Oil Res I

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
