

Technical data sheet

PVC electronic cables · unshielded

LÜTZE ELECTRONIC LiYY

Unshielded electronic cable UL recognized



Identification

Type LIYY 5×0,34
Part No. [108627](#)

Product version

Datasheet version 00

Use/Application/Properties

- | | |
|-------------|---|
| Application | <ul style="list-style-type: none">• In all areas of electronics, measuring, monitoring and regulation technologies• In low voltage switchgear, communications engineering• In dry and damp rooms• For flexible application for free movement and without tensile loading |
| Properties | <ul style="list-style-type: none">• Minimal cable diameter through thin-walled PVC conductor insulation according to UL• Outer jacket special-PVC Class 43 according to UL• Very good oil resistance• Largely resistant to acids and bases• Silicone free |

Construction

Description	ELETRONIC LiYY
Number of conductors/cross-section	5×0.34
Number of conductors	5
Cross-section, metric	0.34 mm ²
Jacket material	Special PVC
Jacket color	grey similar to RAL 7001
Outer Ø	5.8 mm
Outer Ø	0.23 inch
Weight	5.1 kg/100 m
Separating agent	Talcum

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

18.10.2024 • Subject to technical modification

Part No. [108627](#) • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

Technical data sheet

PVC electronic cables · unshielded

Weight	34 Lbs/Mft
Cu-Index	1.7 kg/100 m
Cu-Index	11.4 Lbs/Mft

Construction Element 1

Element construction	5×0.34
Conductor construction	7×0.25
Conductor	CU-wire bare
Conductor category	IEC 60228
Conductor marking	Color coded
Conductor marking standard	DIN 47100
Conductor insulation	Special PVC

Overall construction

Overall stranding	Layered construction
Jacket characteristics	Flame-retardant Oil resistant Acid-resistant Alkali-resistant Silicone free

Technical data

Rated voltage	300 V
Test voltage type	AC 2000 V
Temperature according to UL	80 °C
Temperature range moving	-10 °C ... +70 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	5×D

Technical Data Element 1

Element construction	5×0.34
Insulation resistance at 20 °C	≥20 MΩ×km
Operating capacitance wire-wire	approx.90 pF/m

Certifications/Standards

Certifications	cURus
UL style	AWM 2464
Conformity	CE RoHS REACH
Burning behavior according to	IEC 60332-1 DIN EN 60332-1-2 VDE 0482 322-1-2 UL 1581 part VW-1 Flame Test UL FT1

Technical data sheet

PVC electronic cables · unshielded

General

Note

CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU