

Technical data sheet

Interface Technology · LCIS Relay Module

DC-Relay-Interface, 2 CO contact / DPDT, pluggable

AC / DC 300 V, 8 A, 2000 VA

Push-In, Contact material: AgN



Identification

Type	LCIS2-RSP24DC-PI-2U
Part No.	770053

Product version

Datasheet version	00
-------------------	----

Input

Rated voltage U_N	DC 24 V
Input voltage range	16.8 V – 31.2 V
Rated current I_N	0.018 A
Protection device Input	Free-wheeling diode
Status display input	LED green
Power consumption	0.4 W
Interrupting voltage	<2.4 V

Output

Contact type	2 changeover contacts / DPDT
Min. switching voltage	AC/DC 5 V
Max. switching voltage	AC/DC 300 V
Min. switching current	AC/DC 5 mA
Max. switching current	AC/DC 8 A
Switching capacity DC 13	2 A @ 24 V, 220 mA @ 120 V, 100 mA @ 250 V
Switching capacity AC 15	3 A @ 120 V, 1.5 A @ 240 V
Max. switching capacity	2000 VA
Contact material	AgNi

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

17.03.2023 • Subject to technical modification

Part No. [770053](#) • Datasheet version: 00

page 1 of 4

Technical data sheet

Interface Technology · LCIS Relay Module

Mechanical service life	> 3 x 10 ⁷ operations
Switch-on delay	7 ms
Shutdown delay	3 ms
Protection device	None
Rated insulation voltage (EN 606641- AC 250 V 1)	
Degree of protection	IP20

General

Housing material	PA 6.6
Color of the housing	light grey
Degree of protection	IP20
Mounting	DIN rail mountable TS35 (EN 60715)
Insulation voltage input / output	5.0 kV _{eff}
Safe isolation	yes
Clearance/creepage dist. (control/ load side)	Air clearance: > 10 mm, creepage clearance: > 10 mm
Connection type	Push-In 2 × (0.20 mm ² – 1.5 mm ²)
Dimensions (w × h × d)	15.9 mm × 97.0 mm × 75.8 mm (including mounting bracket)
Weight/unit	0.065 kg
PU (units)	10


General ambient conditions

Operation temperature range	-40 °C ... +70 °C
Storage temperature range	-40 °C ... +85 °C


Certifications/Standards

Certifications	cURus
----------------	-------


Dimensions



PIN assignment



Circuit diagram



DC version