

Technical data sheet

Flexible Premium TPE Control and Tray Cable for Stationary Applications · Unshielded

LUTZE SILFLEX® Tray-ER TPE



Identification

Type	SI TRAY-ER TPE 4×AWG10
Part No.	A3321004

Product version

Datasheet version	00
-------------------	----

Use/Application/Properties

Application	<ul style="list-style-type: none">• Multi-conductor power cable for tray and control applications, with exposed run (open wiring) approval• Metal cutting equipment, machine tools, machine and plant construction, HVAC technology, assembly and production lines, and other industrial applications• Compliant with NFPA 79 requirements• TC-ER for use with cable trays without conduit, which can reduce installation costs in industrial environments• WTTC – wind turbine tray cable rating for use in wind power generation• Dry, damp or wet locations
Properties	<ul style="list-style-type: none">• Crush impact resistant• Gas/vapor-tight sheath per UL 1277• Cutting oil resistant - mineral and bio/vegetable based oil, specially tested with plant based cutting oil.• Non-wicking fillers• Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures• Specially formulated TPE jacket for superior oil resistance• Sunlight resistant• Flame-retardant• Talc free and silicone free

Construction

Description	SILFLEX® TRAY-ER TPE
Number of conductors/cross-section	4×AWG10
Number of conductors	4
Cross-section, metric	6 mm ²
Cross-section AWG	AWG 10
Jacket material	TPE
Jacket color	black similar to RAL 9005

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

Technical data sheet

Flexible Premium TPE Control and Tray Cable for Stationary Applications · Unshielded

Outer Ø	14.6 mm
Outer Ø	0.573 inch
Weight	221 Lbs/Mft
Cu Index	134 Lbs/Mft

Construction Element 1

Element construction	AWG10/4C
Conductor construction	AWG 10 (105/30)
Conductor	AWG conductor CU-wire bare
Conductor category	fine wire Class K
Conductor marking	black • with white number print • green/yellow
Conductor insulation	PVC/Nylon

Overall construction

Jacket characteristics	Oil resistant mineral oil-resistant bio-oil-resistant UV resistant (normal lighting conditions) Silicone-free
------------------------	---

Technical data

Rated voltage U_N	600 V TC-ER 90C 600 V MTW 90C 1000 V WTTC 90C 600 V UL AWM 105 °C
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	4×cable OD

Technical Data Element 1

Element construction	AWG10/4C
----------------------	----------

Approvals/Standards

Approvals	TC-ER cURus cULus UL Type MTW or DP-1 WTTC Meets NEC 336,392 Class 1 Div. 2 per NEC Zone 2 per NEC 501, 502, 505 C(UL) TC and CIC FT4 UL 1277 UL 509 BUS Drop pending
UL style	AWM 21270

Technical data sheet

Flexible Premium TPE Control and Tray Cable for Stationary Applications · Unshielded

Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res I Oil Res II

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--