

Technical data sheet

Load monitoring · LOCC-Box Accessories

LOCC-Box end block



Identification

Type	LOCC-Box-EB 7-6436
Part No.	716436

Product version

Hardware revision	2.0
Datasheet version	03

General

Accessories	End terminal
Housing material	PA 6.6 (UL 94 V-0, NFF I2, F2)
Mounting	DIN rail mountable TS35 (EN 60715)
Degree of protection	IP20 (only as complete system with supply terminal, end block and copper rail cover)
Installation position	Any
Dimensions (w × h × d)	10.0 mm × 110.0 mm × 62.0 mm
Weight/unit	0.01 kg
PU (units)	2

General ambient conditions

Operation temperature range	-25 °C ... +50 °C
Storage temperature range	-40 °C ... +85 °C
Relative air humidity	10 % – 95 %, without condensation
Vibration resistance	4 g acc. to EN 60068-2-6
Shock resistance	15 g acc. EN 60068-2-27

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

22.04.2025 • Subject to technical modification

Part No. [716436](#) • Datasheet version: 03

page 1 of 2

Technical data sheet

Load monitoring · LOCC-Box Accessories

Certifications/Standards

Certifications	cULus (E135145) DNV (TAA0000162)
Standards	UL 60947-5-1 DNV-CG-0339

Dimensions

