

## Technical data sheet

### Flexible Control and Tray Cable TRAY-ER PVC · Shielded

#### LUTZE SILFLEX® N Control Cable (C) PVC For Stationary Applications



#### Identification

Type SI N (C) PVC TRAY-ER (7×AWG10) GR  
Part No. [A3091007](#)

#### Product version

Datasheet version 00

#### Use/Application/Properties

- |             |  |
|-------------|--|
| Application | <ul style="list-style-type: none"><li>• Dual-shielded multi-conductor cable for tray and control applications</li><li>• Machine tools, machine and plant construction, VAC technology as well as other uses.</li><li>• Compliant with NFPA 79 requirements</li><li>• TC-ER-JP for use with cable trays without conduit, which can reduce installation costs in industrial environments</li><li>• WTTC – wind turbine tray cable rating for use in wind power generation</li><li>• Dry, damp or wet locations</li></ul> |
| Properties  | <ul style="list-style-type: none"><li>• Crush impact resistant</li><li>• Gas/vapor-tight sheath per UL 1277</li><li>• Non-wicking fillers</li><li>• Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures</li><li>• Sunlight resistant</li><li>• Flame retardant</li><li>• "direct burial" for installation in the ground</li><li>• Talc free and silicone free</li></ul>  |

#### Construction

Description	SILFLEX® CONTROL CABLE (C) PVC
Number of conductors/cross-section	(7×AWG10)
Number of conductors	7
Cross-section, metric	6 mm <sup>2</sup>
Cross-section AWG	AWG 10

#### United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0  
[www.lutze.com](http://www.lutze.com) • [sales.gb@lutze.co.uk](mailto:sales.gb@lutze.co.uk)

#### Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt  
Tel. +49 (0)7151 6053-0  
[www.luetze.de](http://www.luetze.de) • [info@luetze.de](mailto:info@luetze.de)

24.09.2024 • Subject to technical modification

Part No. [A3091007](#) • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

## Technical data sheet

### Flexible Control and Tray Cable TRAY-ER PVC · Shielded

---

Jacket material	PVC
Jacket color	grey similar to RAL 7001
Outer Ø	17.9 mm
Outer Ø	0.706 inch
Weight	61.9 kg/100 m
Weight	416 Lbs/Mft
Cu-Index	41.2 kg/100 m
Cu-Index	277 Lbs/Mft

---

#### Construction Element 1

---

Element construction	AWG10/7C
Conductor construction	AWG 10 (105/30)
Conductor	AWG conductor CU-wire bare
Conductor category	Fine wire Class K
Conductor marking	black • with white number print • green/yellow
Conductor insulation	PVC/Nylon THHN – THWN

---

#### Overall construction

---

Drain wire	CU-wire tin-plated
Overall shield	Foil shield Aluminium laminate Braid shield Tinned copper wires
Jacket characteristics	Oil resistant Silicone free

---

#### Technical data

---

Rated voltage $U_N$	600 V 90C UL TC-ER-JP 1000 V WTTC 90C 600 V UL MTW 1000 V 105C AWM
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	6×D

---

#### Technical Data Element 1

---

Element construction	AWG10/7C
----------------------	----------

**Technical data sheet**  
**Flexible Control and Tray Cable TRAY-ER PVC · Shielded**

**Certifications/Standards**

Certifications	UL Type MTW or DP-1 Meets NEC 336, 392, 725, 727 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 C(UL) TC and CIC FT4 UL 1277 TC-ER-JP WTTC
UL style	AWM 20886
Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

**General**

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--