

Technical data sheet

PVC electronic cables · unshielded

LÜTZE ELECTRONIC LiYY

Unshielded electronic cable UL recognized



Identification

Type LIYY 2×0,75
Part No. [108648](#)

Product version

Datasheet version 00

Use/Application/Properties

- | | |
|-------------|---|
| Application | <ul style="list-style-type: none">• In all areas of electronics, measuring, monitoring and regulation technologies• In low voltage switchgear, communications engineering• In dry and damp rooms• For flexible application for free movement and without tensile loading |
| Properties | <ul style="list-style-type: none">• Minimal cable diameter through thin-walled PVC conductor insulation according to UL• Outer jacket special-PVC Class 43 according to UL• Very good oil resistance• Largely resistant to acids and bases• Silicone free |

Construction

Description	ELETRONIC LiYY
Number of conductors/cross-section	2×0.75
Number of conductors	2
Cross-section, metric	0.75 mm ²
Jacket material	Special PVC
Jacket color	grey similar to RAL 7001
Outer Ø	5.8 mm
Outer Ø	0.23 inch
Tolerance	±0.2 mm
Weight	4.45 kg/100 m

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

08.03.2023 • Subject to technical modification

Part No. [108648](#) • Datasheet version: 00

page 1 of 3

Technical data sheet

PVC electronic cables · unshielded

Separating agent	Talcum
Weight	30 Lbs/Mft
Cu-Index	1.5 kg/100 m
Cu-Index	10.1 Lbs/Mft

Construction Element 1

Element construction	2×0.75
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 5 Finely stranded DIN VDE 0295 Class 5
Conductor marking	Color coded
Conductor marking standard	DIN 47100
Conductor insulation	Special PVC

Overall construction

Overall stranding	layered construction
Jacket characteristics	Flame-retardant Oil resistant acid-resistant alkali-resistant Silicone-free

Technical data

Rated voltage	300 V
Test voltage type	AC 2000 V
Temperature according to UL	80 °C
Temperature range moving	-10 °C ... +70 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	5×D

Technical Data Element 1

Element construction	2×0.75
Insulation resistance at 20 °C	≥20 MΩ×km
Operating capacitance wire-wire	approx.90 pF/m

Certifications/Standards

Certifications	cURus
UL style	AWM 2464
Conformity	CE RoHS REACH

Technical data sheet

PVC electronic cables · unshielded

Burning behavior according to	IEC 60332-1 DIN EN 60332-1-2 VDE 0482 322-1-2 UL 1581 part VW-1 Flame Test UL FT1
-------------------------------	---

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--