

## Technical data sheet

Flexible VFD Cable Type RHW-2 · shielded

### LUTZE DRIVEFLEX XLPE (C) PVC for Stationary Applications



#### Identification

Type DR XLPE (C) PVC (4×AWG16)  
Part No. [A2161604](#)

#### Product version

Datasheet version 00

#### Use/Application/Properties

Application	<ul style="list-style-type: none"><li>• Dual-shielded motor supply cable to connect power to 3-phase-motors, VFDs and servo drives</li><li>• Cable design for harsh industrial environments and operating conditions with high noise levels</li><li>• Thermoset XLPE offering superior overload and short-circuit temperature</li><li>• Increased wall thickness insulation type RHW-2, offering lower capacitance and higher impedance making it ideal for applications with high voltage spikes and long cable run</li><li>• Compliant with NFPA 79 requirements</li><li>• TC-ER-JP for use with cable trays without conduit, which can reduce installation costs in industrial environments</li><li>• WTTC – wind turbine tray cable rating for use in wind power generation</li><li>• Dry, damp or wet conditions</li></ul>
Properties	<ul style="list-style-type: none"><li>• Flexible XLPE conductors</li><li>• High insulation resistance</li><li>• Low-capacitance cable</li><li>• Effective EMC-compatible shielding thanks to 2-layer shield</li><li>• Specially formulated jacket for oil resistance and easy strip design</li><li>• Non-wicking fillers</li><li>• Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures</li><li>• Crush impact resistant</li><li>• Gas/vapor-tight sheath per UL 1277</li><li>• Sunlight resistant</li><li>• Flame-retardant</li><li>• Direct burial</li><li>• Talc free and silicone free</li></ul>

#### Construction

Description DRIVEFLEX® XLPE (C) PVC  
Number of conductors/cross-section (4GAWG16)

#### USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
[www.lutze.com](http://www.lutze.com) • [info@lutze.com](mailto:info@lutze.com)

17.04.2023 • Subject to technical modification  
Part No. [A2161604](#) • Datasheet version: 00

## Technical data sheet

### Flexible VFD Cable Type RHW-2 · shielded

---

Number of conductors	4
Cross-section, metric	1.5 mm <sup>2</sup>
Cross-section AWG	AWG 16
Jacket material	PVC
Jacket color	black similar to RAL 9005
Outer Ø	12.4 mm
Outer Ø	0.49 inch
Weight	22.2 kg/100 m
Weight	149 Lbs/Mft
Cu Index	57 Lbs/Mft

---

#### Construction Element 1

---

Element construction	AWG16/4C
Conductor construction	AWG 16 (26/30)
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire Class K
Conductor marking	black • with white number print • green/yellow
Conductor insulation	XLPE RHW-2

---

#### Overall construction

---

Drain wire	CU-wire tin-plated
Overall shield	Foil shield tinned copper wires Braid shield optical cover approx. 80 %
Jacket characteristics	Oil resistant Silicone-free

---

#### Technical data

---

Rated voltage U <sub>N</sub>	600 V 90C UL TC-ER-JP 1000 V Flexible VFD servo cable 90C 1000 V WTTC 90C Cable, 1000 V 105C AWM
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	6×cable OD

---

#### Technical Data Element 1

---

Element construction	AWG16/4C
----------------------	----------

## Technical data sheet

### Flexible VFD Cable Type RHW-2 · shielded

---

#### Approvals/Standards

---

Approvals	UL Flexible Motor Supply Cable Flexible VFD Servo Cable TC-ER-JP WTTC UL DP-1 Meets NEC 336,392 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 C(UL) TC and CIC FT4 UL 1277 P-07-KA130021-MSHA
UL style	AWM 20886
Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

#### General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--