

Technical data sheet

PUR servo cables · C-track compatible · shielded

LUTZE SUPERFLEX® PLUS M (C) PUR SERVO 0,6/1 kV
High Flexing Motor Cable for Siemens and other systems
For highest requirements



Identification

Type	SU+ M (C) PUR SE (4G2,5) 90°C
Part No.	111461.1000
SIEMENS designation*	1BB21

Product version

Datasheet version	00
-------------------	----

Use/Application/Properties

Application	• Termination cable motor or motor/brake especially for frequency converters and SERVO drives in machine and plant construction, transport and conveyor technology • Through optimized cable construction optimally suited for continuous flexing applications in C-tracks • Very good resistance against aggressive coolants and lubricants • Especially for industrial environments in mechanical and system engineering
Properties	• High protection against electromagnetic interferences (EMI) • Braided shield optimised for continuous flexing use • Very good alternating bending strength • Low adhesion, abrasion-resistant, nick-resistant, tear-resistant • Hydrolysis-resistant, microbe-resistant, and rot-resistant • Weathering, ozone and UV resistant (normal lighting conditions) • Excellent coolant and lubricant resistance • Largely resistant to oils, greases, alcohol-free benzines and kerosene • Silicone free

Construction

Description	SUPERFLEX® PLUS M (C) PUR SERVO 0,6/1 kV
Number of conductors/cross-section	(4G2,5)
Number of conductors	4
Cross-section, metric	2.5 mm²

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

Technical data sheet

PUR servo cables · C-track compatible · shielded

Jacket material	Special PUR
Jacket color	orange similar to RAL 2003
Outer Ø	10.8 mm
Surface	adhesion-free
Weight	19.09 kg/100 m
Weight	127.91 Lbs/Mft
Cu-Index	13 kg/100 m
Cable construction	Construction without signal pair

Construction Element 1

Element construction	(4G2,5)
Conductor	CU-wire bare
Conductor category	Superfinely stranded DIN VDE 0295 DIN EN 60228, Class 6
Conductor marking	According to system manufacturer
Conductor insulation	PP
Stranding	Conductors twisted without mechanical stress Layer pitch optimised

Overall construction

Overall stranding	Conductors layered construction Conductors twisted without mechanical stress Layer pitch optimised
Overall shield	Braid shield Optical cover approx. 85 %

Technical data

Rated voltage U_0/U	1000
Test voltage type	AC 4000 V
Temperature range moving	-25 °C ... +90 °C
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius moving	7.5×D
Minimum bending radius fixed	5×D
Bending cycles	≥10 Mio
Speed	5 m/s
Acceleration	50 m/s ²
Torsion	± 30°/m

Technical Data Element 1

Element construction	(4G2,5)
Insulation resistance at 20 °C	≥1000 MΩ×km
Operating capacitance wire-wire	105 pF/m
Operating capacitance wire-shield	185 pF/m

Technical data sheet

PUR servo cables · C-track compatible · shielded

Certifications/Standards

Certifications	cURus
UL style	AWM 21209
Conformity	CE RoHS REACH TSCA
Burning behavior according to	IEC 60332-1-1 to 1-3 UL 1581 VW-1 UL FT1
Oil resistant according to	UL 4d100C DIN EN 60811-404
Halogen free according to	IEC 60754-1 DIN EN 60754-1

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU * Cables for MOTION-CONNECT 800PLUS. Siemens, MOTION-CONNECT 800PLUS and Siemens article designations are registered trademarks of Siemens AG.
------	--