

Technical data sheet

Interface Technology · LCIS Solid State Relay

Solid state relay, 2-conductor technology

Switching element DC 60 V / DC 5 A

Screw terminal / Push-In



Identification

Type	LCIS-SR-DC-2L-200130-S
Part No.	763020.0130

Product version

Hardware revision	1.0
Datasheet version	03

Input

Rated voltage U_N	DC 24 V
Input voltage range	DC 19.2 V – 30 V
Rated current I_N	DC 10 mA
Protection device Input	Varistor Reverse diode
Status display input	LED green
Activation voltage	>16.8 V
Interrupting voltage	<14 V

Output

Switching element	MOSFET N/O contact
Min. switching voltage	DC 10 V
Max. switching voltage	DC 60 V
Min. switching current	DC 1 mA
Max. switching current	DC 5 A @ 100 % ED
Inrush current	25 A/20 ms @ 1 Hz

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

Technical data sheet

Interface Technology · LCIS Solid State Relay

Leak current	<1 µA
Switch-on delay	<250 µs @ I _{max}
Shutdown delay	<150 µs @ I _{max}
Protection device	Varistor
Short circuit	Non short-circuit proof
Switching frequency	1 kHz
Degree of protection	IP20

General

Housing material	PA 6.6 (UL 94 V-0)
Color of the housing	RAL 7012 Basalt grey
Degree of protection	IP20
Mounting	DIN rail mountable TS35 (EN 60715)
Installation position	Any
Insulation voltage input / output	4.0 kV _{eff}
Safe isolation	yes
Clearance/creepage dist. (control/ load side)	>5.5 mm
Connection type	Screw terminal Single wire 0.25 mm ² – 2.5 mm ² / AWG 24–14 Fine stranded wire with ferrule 0.25 mm ² – 1.5 mm ² / AWG 24–16
Dimensions (w × h × d)	6.2 mm × 93.0 mm × 73.0 mm
Weight/unit	0.03 kg
PU (units)	5

General ambient conditions

Operation temperature range	-25 °C ... +60 °C
Storage temperature range	-40 °C ... +80 °C
Over voltage category	III
Relative air humidity	20 – 90 % RH, not condensing
Vibration resistance	0.7 g acc. to EN 60068-2-6
Shock resistance	15 g acc. EN 60068-2-27


Certifications/Standards

Conformity	CE UKCA
Certifications	cULus (E135145) DNV (TAA000024Y)
Standards	EN 60947-1 EN 60947-5-1 EN 61000-6-2 EN 61000-6-4 UL 508 DNV-CG-0339


Technical data sheet

Interface Technology · LCIS Solid State Relay

Dimensions



PIN assignment



Use

