

Technical data sheet

Flexible VFD Cable Type RHW-2 · shielded

LUTZE DRIVEFLEX XLPE (C) PVC for Stationary Applications



Identification

Type DR XLPE (C) PVC (4×AWG8)
Part No. [A2160804](#)

Product version

Datasheet version 00

Use/Application/Properties

- | | |
|-------------|---|
| Application | <ul style="list-style-type: none">• Dual-shielded motor supply cable to connect power to 3-phase-motors, VFDs and servo drives• Cable design for harsh industrial environments and operating conditions with high noise levels• Thermoset XLPE offering superior overload and short-circuit temperature• Increased wall thickness insulation type RHW-2, offering lower capacitance and higher impedance making it ideal for applications with high voltage spikes and long cable run• Compliant with NFPA 79 requirements• TC-ER-JP for use with cable trays without conduit, which can reduce installation costs in industrial environments• WTTC – wind turbine tray cable rating for use in wind power generation• Dry, damp or wet conditions |
| Properties | <ul style="list-style-type: none">• Flexible XLPE conductors• High insulation resistance• Low-capacitance cable• Effective EMC-compatible shielding thanks to 2-layer shield• Specially formulated jacket for oil resistance and easy strip design• Non-wicking fillers• Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures• Crush impact resistant• Gas/vapor-tight sheath per UL 1277• Sunlight resistant• Flame-retardant• Direct burial• Talc free and silicone free |

Construction

Description DRIVEFLEX® XLPE (C) PVC
Number of conductors/cross-section (4GAWG8)

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

17.04.2023 • Subject to technical modification
Part No. [A2160804](#) • Datasheet version: 00

Technical data sheet

Flexible VFD Cable Type RHW-2 · shielded

Number of conductors	4
Cross-section, metric	10 mm ²
Cross-section AWG	AWG 8
Jacket material	PVC
Jacket color	black similar to RAL 9005
Outer Ø	23.5 mm
Outer Ø	0.925 inch
Weight	89.7 kg/100 m
Weight	603 Lbs/Mft
Cu Index	295 Lbs/Mft

Construction Element 1

Element construction	AWG8/4C
Conductor construction	AWG 8 (168/30)
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire Class K
Conductor marking	black • with white number print • green/yellow
Conductor insulation	XLPE RHW-2

Overall construction

Drain wire	CU-wire tin-plated
Overall shield	Foil shield tinned copper wires Braid shield optical cover approx. 80 %
Jacket characteristics	Oil resistant Silicone-free

Technical data

Rated voltage U _N	600 V 90C UL TC-ER-JP 1000 V Flexible VFD servo cable 90C 1000 V WTTC 90C Cable, 1000 V 105C AWM
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	6×cable OD

Technical Data Element 1

Element construction	AWG8/4C
----------------------	---------

Technical data sheet

Flexible VFD Cable Type RHW-2 · shielded

Approvals/Standards

Approvals	UL Flexible Motor Supply Cable Flexible VFD Servo Cable TC-ER-JP WTTC UL DP-1 Meets NEC 336,392 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 Submersible Pump C(UL) TC and CIC FT4 UL 1277 P-07-KA130021-MSHA
UL style	AWM 20886
Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--