


Technical data sheet

Suppression Technology · Suppressor for Switched Gear

Universal Suppressor Module

Enclosure type: V1

Protection device: Diode



Identification

Type	LD-V1-0476 DC 24-230V 3A
Part No.	700476

Product version

Datasheet version	00
-------------------	----

Technical data

Type of function	Switching device suppression
Protection device	Diode
Rated voltage U_N	DC 24–230 V
Cut-off peak	≤ 1 V
Inverse voltage/switching current	1300 V / 3 A
Holding Capacity	70 VA
Type of connecting lead	0.5 mm ² LIY
Cable length	0.2 m

General

Design	V1
Potting compound	2-components
Conductor color	blue, red
Housing material	PA 6.6
Color of the housing	grey
Protection class	IP67

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

10.11.2021 • Subject to technical modification

Part No. 700476 • Datasheet version: 00

page 1 of 2



SYSTEMATIC TECHNOLOGY

Technical data sheet

Suppression Technology · Suppressor for Switched Gear

Mounting	DIN rail mounting 1 snap-on socket Attachment hole m 4
Connection type	Fork-type cable lug M 4
Operation temperature range	-20 °C ... +60 °C
Storage temperature range	-20 °C ... +80 °C
Dimensions (w × h × d)	12.5 mm × 25.0 mm × 48.0 mm
Weight/unit	0.017 kg
PU (units)	10


Certifications/Standards

Certifications	cURus (E135145)
----------------	-----------------

Accessories

Accessories	Snap-on socket type 2, grey: Part-No. 700499 DIN rail mounting PU: 10 units
-------------	--

Dimensions



PIN assignment

