

Technical data sheet

Cable fittings and accessories

Metal fitting with shield termination TOP-T-S-EMV2



Identification

Type TOP-T-S-EMV2 MS M20×1,5
Part No. [600372](#)

Product version

Datasheet version 00

Use/Application/Properties

Properties

- Cable fitting with hexagon base
- Strain relief
- Gasket
- O-Ring and EMC compliant shield termination
- The braided shield is automatically contacted when mounting the screw connection.
- metric

Technical data

Clamping range D 6 – 12 mm
Temperature range -20 °C ... +100 °C
Degree of protection IP68
Up to 5 bar
Thread G M20×1.5
SW 1 22 mm
SW 2 22 mm
L 32.3 mm
L1 8 mm

Construction

Description TOP-T-S-EMC2 MS M20 x 1.5

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

18.08.2023 • Subject to technical modification

Part No. [600372](#) • Datasheet version: 00

page 1 of 2



SYSTEMATIC TECHNOLOGY

Technical data sheet

Cable fittings and accessories

Material	Messing vernickelt
Material O-ring	NBR
Material sealing ring	CR

General

PU (units)	50
------------	----

Certifications/Standards

Strain relief according to	EN 62444
----------------------------	----------

Dimensions

