

Technical data sheet

PUR actuator-sensor cables · c-track suitable

LÜTZE SUPERFLEX® TRONIC AS PUR, unshielded
For highest requirements



Identification

Type SU TR AS PUR 8×0,25
Part No. [117242.2000](#)

Product version

Datasheet version 00

Use/Application/Properties

- | | |
|-------------|--|
| Application | <ul style="list-style-type: none">• Connecting cable for the actuator-sensor technology• For continuous flexing use e.g. in c-tracks or free movement in the automation technology, transport and conveyor technology, machine tool manufacture• PUR jacket optimally suited for harsh operating conditions and aggressive coolants and lubricants |
| Properties | <ul style="list-style-type: none">• Very good alternating bending strength• Good pressure and roll-over resistance• Low adhesion, abrasion-resistant, nick-resistant, tear-resistant• Hydrolysis-resistant, microbe-resistant, and rot-resistant• Weathering, ozone and UV resistant (normal lighting conditions)• Industrial and salt water resistant• Excellent coolant and lubricant resistance• Largely resistant to oils, greases, alcohol-free benzines and kerosene• Silicone free• Halogen free |

Construction

Description	SUPERFLEX® TRONIC AS PUR
Number of conductors/cross-section	8×0.25
Number of conductors	8
Cross-section, metric	0.25 mm ²
Cross-section AWG	AWG 24
Jacket material	PUR

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

Technical data sheet

PUR actuator-sensor cables · c-track suitable

Jacket color	black similar to RAL 9005
Outer Ø	5.9 mm
Outer Ø	0.232 inch
Surface	adhesion-free
Weight	4.3 kg/100 m
Weight	28.81 Lbs/Mft
Cu-Index	1.92 kg/100 m
Cu-Index	12.9 Lbs/Mft

Construction Element 1

Element construction	8×0.25
Conductor construction	32×0.10
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Class 6
Conductor marking	individual
Conductor insulation	TPE

Overall construction

Overall stranding	Conductors layered construction Layer pitch optimised Conductors twisted without mechanical stress
Jacket characteristics	Flame-retardant Oil resistant Grease-resistant Petrol-resistant (alcohol-free) Kerosene-resistant Silicone free Halogen free

Technical data

Rated voltage	300 V
Test voltage type	AC 1500 V
Temperature according to UL	80 °C
Temperature range moving	-20 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	7.5×D
Minimum bending radius fixed	4×D
Bending cycles	≥5 Mio
Speed	≤4
Acceleration	≤5

Technical Data Element 1

Element construction	8×0.25
Insulation resistance at 20 °C	≥100 MΩ×km

Technical data sheet

PUR actuator-sensor cables · c-track suitable

Conductor resistance	85.8 Ω /km
Operating capacitance wire-wire	≤ 55 pF/m

Certifications/Standards

Certifications	cURus
UL style	AWM 20549
Conformity	CE RoHS REACH
Burning behavior according to	IEC 60332-2 UL 1581 Horizontal Flame Test CSA FT 1
Oil resistant according to	UL 758 UL 4d100C DIN EN 60811-404
Halogen free according to	EN 60754-1 VDE 0482-754-1
UV-resistant according to	UL 1581/2556-300h

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--