

Technical data sheet

PVC Network cables · ETHERNET · shielded

LÜTZE ELECTRONIC ETHERNET (C) PVC

Cat. 5e



Identification

Type EL ET (C) PVC (4×2×AWG22/7)StC Cat5e
Part No. [104350](#)

Product version

Datasheet version 06

Use/Application/Properties

- | | |
|-------------|--|
| Application | <ul style="list-style-type: none">• For wiring of industrial field bus systems with the globally accepted TCP/IP protocol• For fixed installation or moving use without compulsory guide in the automation technology, transport and conveyor technology, machine tool manufacture• Cable design for harsh industrial environments and operating conditions with high noise levels• Application in automation technology, transport and conveyor technology, machine tool manufacture• Compliant with NFPA 79 requirements |
| Properties | <ul style="list-style-type: none">• High protection against electromagnetic interferences (EMI)• Talc free and silicone free |

Construction

Ethernet Key	SF/UTP
Description	ELECTRONIC ETHERNET (C) PVC
Number of conductors/cross-section	(4×2×AWG22/7)StC
Number of conductors	8
Cross-section, metric	0.34 mm ²
Cross-section AWG	AWG 22
Jacket material	PVC
Jacket color	green similar to RAL 6018
Outer Ø	8.6 mm
Surface	adhesion-free

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

Technical data sheet

PVC Network cables · ETHERNET · shielded

Weight	9.2 kg/100 m
Cu-Index	4.8 kg/100 m

Construction Element 1

Element construction	(4×2×AWG22/7)StC
Conductor construction	AWG 22/7
Conductor	AWG conductor CU-wire tin-plated
Conductor marking standard	ISO IEC 11801
Conductor insulation	Special Polyolefin
Stranding	Conductors stranded in pairs

Overall construction

Overall stranding	Stranded pairs
Overall shield	Aluminium-laminated film shield Braid shield Tinned copper wires Optical cover approx. 85 %
Jacket characteristics	Flame-retardant Oil resistant Silicone free

Technical data

Rated voltage	300 V
Rated voltage U_N	600 V AWM 2570 300 V PLTC
Test voltage type	AC 1000 V
Temperature according to UL	75 °C
Temperature range moving	-25 °C ... +70 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	12×D
Minimum bending radius fixed	6×D
Category	Cat.5e

Technical Data Element 1

Element construction	(4×2×AWG22/7)StC
Insulation resistance at 20 °C	≥5000 MΩ×km
Operating capacitance wire-wire	approx.50 pF/m
Loop resistance	≤114.8 mΩ/m
Impedance	nom.100 Ω

Certifications/Standards

Certifications	cULus PLTC cURus CMX Outdoor-CMG
----------------	---

Technical data sheet

PVC Network cables · ETHERNET · shielded

UL style	AWM 2570
Conformity	CE RoHS REACH
Burning behavior according to	DIN EN 60332-1-2 DIN EN 60332-3-24 UL 1685 UL FT4
Oil resistant according to	Oil Res I

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--