

Technical data sheet

Cable fittings and accessories

Metal fitting with shield termination TOP-T-S-EMV1



Identification

Type	TOP-T-S-EMV1 MS M25
Part No.	600173

Product version

Datasheet version	00
-------------------	----

Use/Application/Properties

Properties	• Cable fitting with hexagon base • Strain relief • Gasket • O-Ring and EMC compliant shield termination • Simple installation - the shield braiding with plastic insert is pressed against fitting base.
------------	---

Technical data

Clamping range D	11 – 18 mm
Temperature range	-30 °C ... +100 °C
Degree of protection	IP66 IP68 Up to 5 bar IP69K
d	15 mm
Thread form	Metric
Thread G	M25×1.5
SW	30 mm
L	38 mm
L1	7 mm

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

31.03.2025 • Subject to technical modification

Part No. [600173](#) • Datasheet version: 00

page 1 of 2

Technical data sheet

Cable fittings and accessories

Construction

Description	TOP-T-S-EMV1 MS M25 SW30
Material	Messing vernickelt
Material O-ring	NBR
Material sealing ring	CR

General

PU (units)	25
------------	----

Certifications/Standards

Strain relief according to	EN 62444
----------------------------	----------

Dimensions

