

Technical data sheet

Suppression Technology · Valve suppressors

Adjustable male, form BI (11 mm)

Ground wire terminator (PE) adjustable in 180° steps

Protection device: Varistor+LED



Identification

Type	LV-V22-5832 AC/DC 110-230V
Part No.	705832

Product version

Datasheet version	00
-------------------	----

Technical data

Type of function	Valve suppressor
Protection device	Varistor + LED
Rated voltage U_N	AC/DC 110–230 V
Nominal voltage range	AC/DC 110 V – 230 V
Current Consumption	4 mA
Cut-off peak	≤ 475 V
Rated frequency f_N	50 Hz / 60 Hz
Connecting lead $\varnothing$	4 – 9 mm

General

Design	BI Ind. (11 mm)
Status indication	LED yellow
Amperage range	≤ 1 A
Contact resistance	< 15 m Ω
Insulation resistance	> 100 M Ω
Pole number	3
Housing material	PA
Color of the housing	transparent

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

Technical data sheet


Suppression Technology · Valve suppressors

Contact material	CuZn silver-plated
Material seal	NBR
Material sealing ring	NBR
Mechanical service life	>100 insertion cycles
Degree of pollution	3
Protection class	IP67
Mounting	Breakaway torque 0.4 Nm
Connection type	Screw terminal
Connection cross-section	max. 1.5 mm ²
Connection cross-section	max. AWG 16
Operation temperature range	-40 °C ... +90 °C
Storage temperature range	-40 °C ... +90 °C
Dimensions (w × h × d)	21.0 mm × 30.3 mm × 51.0 mm
Weight/unit	0.021 kg
PU (units)	1

Certifications/Standards

Certifications	cURus (E256031)
----------------	-----------------

Dimensions



PIN assignment

