

Technical data sheet

Cable fittings and accessories

Plastic fittings TOP-T-P, metric version



Identification

Type TOP-T-P M12×1,5 GR
Part No. [600790](#)

Product version

Datasheet version 00

Use/Application/Properties

Properties

- metric
- Cable fitting with hexagon base
- Strain relief and seal

Technical data

Clamping range D 2 mm – 6.5 mm
Temperature range -20 °C ... +100 °C
Degree of protection IP68
Up to 5 bar
Thread form metric
Thread G M12×1.5
SW 15 mm
L1 8 mm

Construction

Description TOP-T-P M12×1.5 GR
Material PA 6.6-V-2
Material sealing ring Neoprene
Color silver grey RAL 7001

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

19.04.2023 • Subject to technical modification

Part No. [600790](#) • Datasheet version: 00

page 1 of 2

Technical data sheet
Cable fittings and accessories

General

PU (units) 100

Certifications/Standards

Certifications UR

Dimensions

