

Technical data sheet

PUR Bus cables · Profibus · C-track compatible

LÜTZE SUPERFLEX® Profibus (C) PUR UL For highest requirements



Identification

Type SU PROFIBUS(C) PUR (3G0,75+1×2×AWG24/19)
Part No. [104275](#)

Product version

Datasheet version 00

Use/Application/Properties

- | | |
|-------------|---|
| Application | <ul style="list-style-type: none">• For wiring of industrial field bus systems like PROFIBUS DP, SINEC L2, F.I.P• For continuous flexing use e.g. in c-tracks or free movement in the automation technology, transport and conveyor technology, machine tool manufacture• Compatible with all major drag chain brands• Compliant with NFPA 79 requirements |
| Properties | <ul style="list-style-type: none">• High protection against electromagnetic interferences (EMI)• Silicone free• Flame retardant• Abrasion-resistant, nick-resistant, tear-propagation-resistant• Hydrolysis-resistant, microbe-resistant, and rot-resistant• Coolant and lubricant resistant |

Construction

Description	SUPERFLEX® PROFIBUS (C) PUR
Number of conductors/cross-section	(3G0,75+(1×2×AWG24/19)St)
Number of conductors	5
Cross-section, metric	0.25 mm²
Cross-section AWG	AWG 24
Jacket material	PUR
Jacket color	violet similar to RAL 4001
Outer Ø	9.8 mm
Outer Ø	0.386 inch
Surface	adhesion-free
Weight	14.4 kg/100 m
Weight	97 Lbs/Mft
Cu Index	6.6 kg/100 m

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222
www.lutze.com • info@lutze.com

Technical data sheet

PUR Bus cables · Profibus · C-track compatible

Cu Index	44 Lbs/Mft
----------	------------

Construction Element 1

Element construction	3G0.75
Conductor	CU-wire bare
Conductor marking standard	EN 61158, EN 61784
Conductor insulation	TPE

Construction Element 2

Element construction	(1×2×AWG24/19)
Conductor	AWG conductor
Conductor marking standard	EN 61158, EN 61784
Conductor insulation	Foamed PP
Element shielding	Aluminium laminate Foil shield

Overall construction

Overall stranding	Elements stranded together
Overall shield	Foil shield Braid shield Tinned copper wires Optical cover approx. 85 %
Jacket characteristics	Silicone free Halogen free Flame-retardant

Technical data

Rated voltage	300 V
Test voltage type	AC 1500 V
Temperature according to UL	80 °C
Temperature range moving	-30 °C ... +70 °C
Temperature range fixed	-40 °C ... +80 °C
Minimum bending radius moving	7.5×cable OD
Minimum bending radius fixed	5×cable OD

Technical Data Element 1

Element construction	3G0.75
----------------------	--------

Technical Data Element 2

Element construction	(1×2×AWG24/19)
Operating capacitance wire-wire	approx.30 pF/m
Loop resistance	≤165 mΩ/m
Impedance	nom.150 Ω

Technical data sheet

PUR Bus cables · Profibus · C-track compatible

Approvals/Standards

Approvals	CMX cULus cURus
UL style	AWM 21198
Conformity	CE RoHS REACH TSCA
Burning behavior according to	IEC 60332-1 DIN EN 60332-1-2 UL 1581 UL FT1
Halogen free according to	DIN EN 60754-1 IEC 60754-1

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--