

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Shielded

LUTZE SILFLEX® N Control Cable (C) PVC For Stationary Applications



Identification

Type SI N (C) PVC TRAY-ER (7×AWG20) GR
Part No. [A3092007](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Dual-shielded multi-conductor cable for tray and control applications
 - Machine tools, machine and plant construction, VAC technology as well as other uses.
 - Compliant with NFPA 79 requirements
 - PLTC-ER Power Limited Tray Cable – Exposed Run
 - ITC-ER Instrumentation Tray Cable – Exposed Run
 - Dry, damp or wet locations
- Properties
- Crush impact resistant
 - Gas/vapor-tight sheath per UL 1277
 - Non-wicking fillers
 - Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
 - Sunlight resistant
 - Flame retardant
 - Talc free and silicone free

Construction

Description SILFLEX® CONTROL CABLE (C) PVC
Number of conductors/cross-section (7×AWG20)
Number of conductors 7
Cross-section, metric 0.5 mm²
Cross-section AWG AWG 20
Jacket material PVC
Jacket color grey similar to RAL 7001
Outer Ø 9.1 mm
Outer Ø 0.36 inch
Weight 13.7 kg/100 m
Weight 92 Lbs/Mft

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222
www.lutze.com • info@lutze.com

26.09.2024 • Subject to technical modification

Part No. [A3092007](#) • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Shielded

Cu Index	5.4 kg/100 m
Cu Index	36 Lbs/Mft

Construction Element 1

Element construction	AWG20/7C
Conductor construction	AWG 20 (10/30)
Conductor	AWG conductor CU-wire bare
Conductor category	Fine wire Class K
Conductor marking	black · with white number print · green/yellow
Conductor insulation	PVC/Nylon THHN – THWN

Overall construction

Drain wire	CU-wire tin-plated
Overall shield	Aluminium laminate Foil shield Braid shield Tinned copper wires
Jacket characteristics	Oil resistant Silicone free

Technical data

Rated voltage U_N	300 V 90C PLTC-ER 300 V 90C ITC-ER 600 V UL MTW 1000 V 105C AWM
Temperature range fixed	-40 °C ... +105 °C
Minimum bending radius fixed	6×cable OD

Technical Data Element 1

Element construction	AWG20/7C
----------------------	----------

Approvals/Standards

Approvals	UL Type MTW or DP-1 Meets NEC 336, 392, 725, 727 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 C(UL) TC and CIC FT4 UL 1277 PLTC-ER ITC-ER
UL style	AWM 20886
Conformity	CE RoHS REACH TSCA

Technical data sheet

Flexible Control and Tray Cable TRAY-ER PVC · Shielded

Oil resistant according to Oil Res II

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU