Technical data sheet
Cable fittings and accessories

Metal fitting TOP-T

Identification

Type	TOP-T MS M25×1,5
Part No.	600762

Product version

Datasheet version	00

Use/Application/Properties

Properties	• Cable fitting with hexagon base • Strain relief • Gasket and O-Ring

Technical data

Clamping range D	11 – 18 mm
Temperature range	-30 °C … +100 °C
Degree of protection	IP66 IP68 Up to 5 bar IP69K
Thread form	Metric
Thread G	M25×1.5
SW 1	30 mm
SW 2	30 mm
L	35 mm
L1	7 mm

Construction

Description	TOP-T MS M25×1.5 SW30

United Kingdom: LÜTZE Ltd.
Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH
Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0
www.luetze.de • info@luetze.de

Material	Messing vernickelt
Material O-ring	NBR
Material sealing ring	CR
Material clamping insert	PA 6

General

PU (units)	25

Certifications/Standards

Strain relief according to	EN 62444

Dimensions